



Notified Body No. 0370

CERTIFICATE



No.

0370-CPR-1183

CERTIFICATE OF CONSTANCY OF PERFORMANCE

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

FIRE DETECTION AND FIRE ALARM SYSTEMS.

PART 11: MANUAL CALL POINTS

ADDRESSABLE MANUAL CALL POINT. MODEL: MAD-450

Place on the market under the name of:

DETNOV SECURITY, S.L.

C/ DE LA CIÈNCIA, 30 08840 VILADECANS (BARCELONA - SPAIN)

And produced in the manufacturing plant:

C/ DE LA CIÈNCIA, 30 08840 VILADECANS (BARCELONA - SPAIN)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 54-11:2001, EN 54-11:2001/A1:2005

under system 1 are applied and that the product fulfils all the prescribed requirements set out above.

This certificate was first issued on 10^{th} June 2011 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly. It is confirmed on 17^{th} July 2020.

The monitoring assessment will be done before 30th September 2021

Bellaterra, 17th July 2020

Applus LGAI Technological Center, S.A.

Xavier Ruiz Peña

Managing Director, Product Conformity B.U.

This document is not valid without its technical annex; whose number coincides with the number of certificate.

You can check the validity of this certificate into our website at: https://apps.applus.com/microsites/microsites/FECIP/login



LGAI Technological Center, S.A. (APPLUS) Campus UAB s/n – Ronda de la Font del Carme, s/n E - 08193 Bellaterra (Barcelona) T +34 93 567 20 00 www.appluslaboratories.com



Technical Annex Ed. 4 18/10/2013

0370-CPR-1183

Annex according to EN 54-11:2001, EN 54-11:2001/A1:2005

| ESSENTIAL CHARACTERISTICS | CLAUSES IN THIS EUROPEAN STANDARD | MANDATED LEVEL(S) OR CLASS(ES) |
|--|--------------------------------------|-----------------------------------|
| Marking and data | 4.2 | PASS |
| Normal condition | 4.3.1 | PASS |
| Alarm condition | 4.3.2 | PASS |
| Indicators for alarm condition | 4.4 | PASS |
| Reset facility | 4.5 | PASS |
| Test facility | 4.6 | PASS |
| Shape, dimensions and colours | 4.7.2 | PASS |
| Symbols and lettering | 4.7.3 | PASS |
| Protection against accidental operation | 4.7.4 | PASS |
| Environment category | 4.7.5 | PASS |
| Additional requirements for software controlled manual call points | 4.8 | NA |
| Operational performance test | 5.2 | PASS |
| Function test | 5.3 | PASS |
| Test facility test (operational) | 5.4 | PASS |
| Reliability test (endurance) | 5.5 | PASS |
| Variation of supply parameters | 5.6 | PASS |
| Dry heat (operational) | 5.7 | PASS |
| Dry heat (endurance) | 5.8 | NA |
| Cold (operational) | 5.9 | PASS |
| Damp heat, cyclic (operational) | 5.10 | PASS |
| Damp heat, cyclic (endurance) | 5.11 | NA |
| Damp heat, steady state (endurance) | 5.12 | PASS |
| SO2 corrosion (endurance) | 5.13 | PASS |
| Shock (operational) | 5.14 | PASS |
| Impact (operational) | 5.15 | PASS |
| Vibration, sinusoidal (operational) | 5.16 | PASS |
| Vibration, sinusoidal (endurance) | 5.17 | PASS |
| Electromagnetic compatibility (EMC) (operational) | 5.18 | PASS |
| Enclosure protection | 5.19 | NA |

PASS; NPD = No Performance Determined, NA = Not Apply